



## WDE-168S

### Commercial Dehumidifier

#### Features:

- Standard colour sheet metal casing, Anti corrosion evaporator and condenser.
- Dual drainage System with 6 ltrs tank and pump and external hose
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- Continuous drainage option available.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

#### Technical Specification: -

- |  |   |  |
|--|---|--|
| • Model No.:                             | - | WDE-168P   |
| • Moisture removal 30°C, 80%R.H.:        | - | 168L/Day   |
| • Power supply V/Hz:                     | - | 220~240V/50Hz                                    |
| • Rated Power consumption 30°C, 80%R.H.: | - | 2820W  |
| • Control Type;                          | - | Electric   |
| • Maintain level:                        | - | 30% R.H.- 80% R.H.                               |
| • Current 30°C, 80%R.H.:                 | - | 12A  |
| • Air flow/Air Circulation:              | - | 2000m3/hr  |
| • Ambient Temperature for operation:     | - | 5-38°C   |
| • Approx. Cover Area*:                   | - | 200-240m <sup>2</sup> (room height =2.6m)        |
| • Water tank capacity:                   | - | 6 Litres   |
| • Noise level:                           | - | 60 dB(A)   |
| • Refrigerant:                           | - | R410   |
| • Net Weight:                            | - | 108 kgs  |
| • Body dimensions (H x W x D):           | - | 1600 x 410 x 600 mm / 62.99 x 16.14 x 23.62 inch |