

# WATER COOLERS

STAINLESS  
STEEL TOP



Quench your thirst for chilled water with Voltas Water Coolers. A Stainless Steel 304 and reciprocating tropicalized compressor, housed in a vertical design for near-instant optimum cooling. Never run out of cool water again.



## TECHNICAL SPECIFICATIONS - WATER COOLER

Model	20/20 PSS & FSS	20/40 PSS & FSS	40/40 PSS & FSS	40/80 PSS & FSS	60/80 PSS & FSS	60/120 PSS & FSS	150/150 PSS & FSS-Recip. / Rotary Compressor	150/300 PSS & FSS
Storage Capacity (Ltrs)	20	40	40	80	80	120	150	300
Cooling Capacity (Ltrs/hour)	20	20	40	40	60	60	150	150
Cabinet Material	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS
Storage Tank Material	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304
Number Of Fucets	1	1	2	2	2	2	2	5 [3+2 OPTIONAL]
Compressor	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A
Temperature Range	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C
Refrigerant	R- 134 a	R- 134 a	R - 134a	R-134a	R-134a	R-134a	R - 22	R - 134a
Over All Product Dimensions With Trough (Wxdxh) Mm	364 X 505 X 1117	461 X 582 X 1217	461 X 582 X 1217	461 X 582 X 1441	461 X 582 X 1441	564 X 705 X 1397	564 X 705 X 1521	1250x890x1500

## SPECIALIZED WATER COOLERS

Model	20/40 PSS & FSS-NCW	40/80 PSS & FSS-NCW	40/80 PSS & FSS-UV	40/80 PSS & FSS-UV+NCW	60/120 PSS & FSS-UV	150/150 PSS & FSS-UV
Storage Capacity (Ltrs)	40	80	80	80	120	150
Cooling Capacity (Ltrs/Hour)	20	40	40	40	60	150
Cabinet Material	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS
Storage Tank Material	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304
Number Of Fucets	2=1+1 [1 NORMAL+1 COLD]	2=1+1 [1 NORMAL+1 COLD]	2=1+1 [1 NORMAL+1 COLD]	2=1+1 [1 NORMAL+1 COLD]	2	2
Compressor	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R22A
Temperature Range	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C
Refrigerant	R- 134 a	R-134a	R-134a	R-134a	R-134a	R - 22
Over All Product Dimensions With Trough (Wxdxh) Mm	461 X 582 X 1217	461 X 582 X 1441	461 X 582 X 1441	461 X 582 X 1441	564 X 705 X 1397	564 X 705 X 1521

Note:- \* R-134a gas will be available in Selected models for GEMS



Soft Aesthetic Design



Longer Cooling Retention.



Compact Design



Safety Compliant



Upto 40% Electricity Saving



Eco-Friendly Gas Refrigerant



Anti-corrosive Pre-coated Body



Energy Efficient Compressor



Tropicalized Machines



In-situ Puf Insulation