

Professional
Cooling
By
Cool
Professional



Kitchen Refrigeration - Reach-in & Counters - Static & Frost Free



CGN 650 TNM / BTM
RI 551 C2/F2



CGN 1410 TNM / BTM
RI 1101 C4/F4



CGN 2100 TN / BT



CS 900



CPS 200



CSH 3000

Elanpro Professional Reach Ins and Under counters for refrigeration or freezer application are designed to meet the tough Indian Kitchen Conditions. Our machines are tested to perform in ambient environment of 43°C and presents a host of exciting new features.

Key Features:

- Dixell digital controller
- Removable gasket
- Adjustable shelves
- Heavy duty lockable castors
- Lock
- Built in handle
- Environment Friendly Refrigerant
 - R134A for Chillers
 - R404A for Freezers

Optional Features:

- Left or Right hinged door
- Single or multi door
- Heavy duty adjustable SS legs

Common - All Models

- HACCP Compliance
- Adjustable Feet

	Model	Description	Capacity (Ltrs)	Dimension (WxDxH) mm	Temperature Range	GN Compatibility	No. of Shelves	Climate Class	Inside SS
FROST FREE	CGN 650 TNM	2 Door Reach-in Chiller	650	740 x 830 x 2010	2°C ~ 8°C	2 x GN 1/1	3	43°C	SS 430
	CGN 650 BTM	2 Door Reach-in Freezer	650	740 x 830 x 2010	-18°C ~ -22°C	2 x GN 1/1	3	43°C	SS 430
	CGN 1410 TNM	4 Door Reach-in Chiller	1410	1480 x 830 x 2010	2°C ~ 8°C	2 x GN 1/1	6	43°C	SS 430
	CGN 1410 BTM	4 Door Reach-in Freezer	1410	1480 x 830 x 2010	-18°C ~ -22°C	2 x GN 1/1	6	43°C	SS 430
	CGN 2100 TN	2 Door Under Counter Chiller	265	1360 x 700 x 850	2°C ~ 8°C	1 x GN 1/1	2	38°C	SS 430
	CGN 3100 TN	3 Door Under Counter Chiller	400	1795 x 700 x 850	2°C ~ 8°C	1 x GN 1/1	3	38°C	SS 430
	CGN 2100 BT	2 Door Under Counter Freezer	265	1360 x 700 x 850	-18°C ~ -22°C	1 x GN 1/1	2	38°C	SS 430
	CGN 3100 BT	3 Door Under Counter Freezer	400	1795 x 700 x 850	-18°C ~ -22°C	1 x GN 1/1	3	38°C	SS 430
	CSH 2000	2 Door Salad Under Counter with Prep Table	337	1510 x 800 x 1085	2°C ~ 8°C	6 x GN 1/3	2	38°C	SS 430
	CSH 3000	3 Door Salad Under Counter with Prep Table	497	2020 x 800 x 1085	2°C ~ 8°C	10 x GN 1/3	3	38°C	SS 430
STATIC	RI 551 C	2 Door Reach-in Chiller	550	680 x 710 x 2000	2°C ~ 8°C	NA	3	43°C	SS 201
	RI 1101 C	4 Door Reach-in Chiller	1100	1340 x 710 x 2000	2°C ~ 8°C	NA	6	43°C	SS 201
	RI 551 F	2 Door Reach-in Freezer	550	680 x 710 x 2000	-10°C ~ -20°C	NA	3	43°C	SS 201
	RI 1101 F	4 Door Reach-in Freezer	1100	1340 x 710 x 2000	-10°C ~ -20°C	NA	6	43°C	SS 201
	UC 1501 C	2 Door Undercounter Chiller	265	1360 x 600 x 850	2°C ~ 8°C	NA	2	38°C	SS 201
	UC 1801 C	3 Door Undercounter Chiller	400	1795 x 600 x 850	2°C ~ 8°C	NA	3	38°C	SS 201
	CS 900	2 Door Salad Under Counter	240	900 x 700 x 970	2°C ~ 8°C	NA	2	32°C	SS 430
	CS 903	3 Door Salad Under Counter	360	1365 x 700 x 970	2°C ~ 8°C	NA	3	32°C	SS 430
	CPS 200	2 Door Salad Under Counter with Prep Table	240	900 x 700 x 970	2°C ~ 8°C	5 x GN 1/6	2	32°C	SS 430
	CPS 300	3 Door Salad Under Counter with Prep Table	360	1365 x 700 x 970	2°C ~ 8°C	8 x GN 1/6	3	32°C	SS 430

Specifications, features and colours are subject to change without any notice, due to continuous product development. GN pan are optional and not supplied with the equipments.

Kitchen Refrigeration - Reach-in, Salad & Prep Counters

Elanpro Professional Reach Ins for refrigeration or freezer application are designed to meet the tough Indian Kitchen Conditions. Our machines are tested to perform in ambient environment of 43°C and presents a host of exciting new features.



EGN 650 C2/F2

EGN 1410 C4/F4



EGN 2100 C/F



EGN 3V



Frost Top 3F



EVRX 1200 / EVRX 1400

Key Features:

- DANFOSS/EMBRACO compressor
- Dixell digital controller
- EBM Fan Motor
- Removable gasket
- Adjustable shelves
- Heavy duty lockable castors
- Lock
- Built in handle

- Environment Friendly Refrigerant
 - R134A for Chillers
 - R404A for Freezers

Optional Features:

- Left or Right hinged door
- Single or multi door
- Heavy duty adjustable SS legs

Common - All Models

- HACCP Compliance
- Adjustable Feet

Model	Description	Capacity (Ltrs)	Dimension (WxDxH) mm	Temperature Range	GN Compatibility	No. of Shelves	Climate Class	Inside SS
EGN 650 C2	2 Door Reach In Chiller	650	740 x 835 x 2010	-2°C ~ 8°C	2 x GN 1/1	3	43°C	SS 304
EGN 1410 C4	4 Door Reach In Chiller	1410	1480 x 835 x 2010	-2°C ~ 8°C	2 x GN 1/1	6	43°C	SS 304
EGN 650 F2	2 Door Reach In Freezer	650	740 x 835 x 2010	-10°C ~ -20°C	2 x GN 1/1	3	43°C	SS 304
EGN 1410 F4	4 Door Reach In Freezer	1410	1480 x 835 x 2010	-10°C ~ -20°C	2 x GN 1/1	6	43°C	SS 304
EGN 600 Fish®	Reach In Fish Chiller	600	680 x 810 x 2000	-2°C ~ 8°C	NA	5	40°C	SS 304
EGN 2100 C	2 Door Undercounter Chiller	265	1360 x 700 x 860	-2°C ~ 8°C	1 x GN 1/1	2	38°C	SS 304
EGN 3100 C	3 Door Undercounter Chiller	400	1795 x 700 x 860	-2°C ~ 8°C	1 x GN 1/1	3	38°C	SS 304
EGN 2100 F	2 Door Undercounter Freezer	265	1360 x 700 x 860	-10°C ~ -20°C	1 x GN 1/1	2	38°C	SS 304
EGN 3100 F	3 Door Undercounter Freezer	400	1795 x 700 x 860	-10°C ~ -20°C	1 x GN 1/1	3	38°C	SS 304
Frost Top 3F	Frost Top	NA	1102 x 678 x 430	-10°C	NA	NA	38°C	SS 304
EGN 3V	Ventilated Cooling Well	NA	1102 x 678 x 533	2°C ~ 8°C	3 x GN 1/1	NA	32°C	SS 304
EVRX 1200	Salad Display Counter	NA	1200 x 335 x 225	2°C ~ 8°C	5 x GN 1/4	NA	32°C	SS 304
EVRX 1400	Salad Display Counter	NA	1400 x 335 x 225	2°C ~ 8°C	6 x GN 1/4	NA	32°C	SS 304

Kitchen Refrigeration - Flexi Drawer Undercounter

Elanpro Flex drawer are designed to save space and enhance user experience at a touch of a button. The unique convertible feature helps in converting freezer to fridge and vice versa.



CBR - 1



CBR - 2

Key Features:

- CFC Free Refrigerant
- User friendly controls with LED Temperature display
- Change drawer temperature from fridge to freezer at the touch of a button
- Auto energy saving hot gas defrost
- Removable gasket for easy cleaning
- GN 1/1 – 150 mm deep pan capacity maximizes available storage space
- Tropicalized to perform at 40°C ambient

Model	Description	Capacity (Ltrs)	Dimension (WxDxH) mm	Temperature Range	GN Compatibility
CBR 1-2	Flexi Drawer Counter	78	905 x 700 x 565	1°C ~ 4°C / -18°C ~ -21°C	2xGN 1/1
CBR 1-3	Flexi Drawer Counter	116	1230 x 700 x 565	1°C ~ 4°C / -18°C ~ -21°C	3xGN 1/1
CBR 2-2	Flexi Drawer Counter	179	905 x 700 x 830	1°C ~ 4°C / -18°C ~ -21°C	4xGN 1/1
CBR 2-3	Flexi Drawer Counter	262	1230 x 700 x 830	1°C ~ 4°C / -18°C ~ -21°C	6xGN 1/1

Manufactured as per European Technology and Standards

GN Pan are optional

Blast Chillers & Freezers

Deep-Freezing or Freezing

These two terms are often confused but the end result is the same in both cases: the temperature of a food product is lowered but the water contained in it does not freeze completely. The difference is that with freezing there are no time limits and macro crystals are formed internally, whereas deep-freezing means reaching a temperature of -18°C in the centre of the product within 4 hours, avoiding the formation of macro crystals.



Blast Chillers:

Why is it Necessary to use?

All fresh organic food products contain a natural bacterial load which, in favourable ambient conditions (temperature and humidity), multiplies producing hazardous effects on consumer health.

The most dangerous thermal threshold is between +65°C and +35°C: in this temperature range, bacterial multiplication is accelerated. Micro-organisms begin to develop between +35°C and +10°C.

Blast chilling means lowering the temperature in the centre of the product from +70°C to +4°C as quickly as possible, and in any case within 90 minutes. Blast chilling of a cooked product not only prevents bacterial proliferation but also prolongs product conservation time. The quality of the food is not affected, and the product can be stored up to a couple of month.



Shock Freezers 70°C to -18°C

The maximum storages is achieved through the rapid production of cold to allow the production of micro crystals that optimally preserve the cells of the foodstuff.

The Shock Freezing drops the temperature from 70°C to -18°C in a maximum time of 240 minutes.

The food is quickly frozen and then be kept for months in normal freezer.



DI4



D3

Key Features:

- CFC refrigerant and foam
- Complete structure interior & exterior in stainless steel with round internal edges for easy cleaning
- Self closing doors with easy to clean and replace magnetic balloon gasket
- Replaceable Electric door mullion heater
- 75mm thickness insulation for excellent thermal efficiency
- Ventilated refrigeration compartment
- Dixell controller and compact footprints
- Danfoss refrigeration components
- EBM Fan

Model	Dimension (WxDxH) mm	Capacity Ltrs	Cooling Capability*	Tray*	Power Supply	Cooling Mode
T3	660 x 650 x 430	39	8 kg / 5 kg	3	230 V / 50 Hz	Ventilated
D3	800 x 815 x 945	139	12 kg / 8 kg	3	230 V / 50 Hz	Ventilated
D5	800 x 815 x 1015	169	18 kg / 14 kg	5	230 V / 50 Hz	Ventilated
D10	800 x 815 x 1645	368	40 kg / 28 kg	10	230 V / 50 Hz	Ventilated
D14	800 x 815 x 2170	494	55 kg / 38 kg	14	380 V / 50 Hz	Ventilated

Specifications, features and colours are subject to change without any notice, due to continuous product development.

* 70/3°C in 90 minute & 70/-18°C in 240 minute.

Hospitality Solutions - Bar Refrigeration

Elanpro Wine Chillers are known for their aesthetics and ease of operation, pull out wooden shelf helps in storage and selection of wine. Twin cabinet with individual temperature control ensures your White and Red wine are perfectly maintained to offer you the experience of Wine at any time. Elanpro back bar come in Black & SS finish.



EBB 2D/2D SS



GF5G



EBB 3D/3D SS



EGN 2100 CG

Key Features - Wine Chillers

- Two separate zones for Red and White wine
- Actual and set temperature display
- Lock
- No frost
- Anti-Vibration
- Elegant stainless steel door frame
- Blue LED Light
- Double layer anti UV tinted glass door
- Cabinet colour: Black
- Pullout sliding shelves
- Beach wooden shelves
- Charcoal filter



EWG 131 D

Particulars	GF 5G	EBB 2D/2D SS	EBB 3D/3D SS	EGN 2100 CG	EGN 3100 CG	EWG 51 D	EWG 131 D
Descriptions	1 Door Glass Froster	2 Door Back Bar	3 Door Back Bar	Under Counter Bar	Under Counter Bar	Wine Cooler	Wine Cooler
Dimension (WxDxH) mm	595 x 525 x 875	900 x 514 x 870	1350 x 514 x 870	1360 x 700 x 860	1795 x 700 x 860	595 x 575 x 820	595 x 680 x 1417
Capacity	100 Ltrs.	223 Ltrs.	335 Ltrs.	265 Ltrs.	400 Ltrs.	46 Bottles	128 Bottles
Power Consumption (W)	280	230	320	396	514	113	175
Temperature Range	-10°C ~ -15°C	2°C ~ 8°C	2°C ~ 8°C	2°C ~ 8°C	2°C ~ 8°C	5°C ~ 12°C 12°C ~ 22°C	5°C ~ 12°C 12°C ~ 22°C
No of Shelf	2	2	3	2	3	6	11
Castors	No	No	No	Yes	Yes	No	No
Lock	No	Yes	Yes	No	No	Yes	Yes

Specifications, features and colours are subject to change without any notice, due to continuous product development.

Wide Range of Beer & Beverage Cooling Solutions

Elanpro is known for its pioneer presence in Draft beer solution with most innovative range of Towers in Brass, Copper, SS, Raisin and Ceramic finish with Illuminated and non-illuminated branding option. The cooling solution starts from single line upto 16 lines to meet any type of Beer installation requirements. With over 5000 installations in the country Elanpro today has dominating presence in Draft beer segment.



Old Brewery (4-8)



Sexy

Flute

Lucky

Shield



Mini Lady



HE 90 / 120

Cooling unit to dispense extra cold beer between 0°C & 2°C and to frost the tower

Model	Dimension (WxDxH) mm	Compressor	Tank Capacity Ltrs.	Ice Bank (Kgs)	No. of Coils/Length	Rate of Drink Per/Min (200 ml)	Cooling Capacity*
Mini Lady	407 x 407 x 280	1/6 Hp	12	4	1-2/8 Mtrs.	2 Glass	25 Ltrs./Hr.
HE 90	390 x 390 x 720	1/3 Hp	36	14	1-4/17 Mtrs.	8 Glass	90 Ltrs./Hr.
HE 120	450 x 450 x 800	1/2 Hp	50	25	1-8/22 Mtrs.	10 Glass	120 Ltrs./Hr.
HE 250	520 x 820 x 870	3/4 Hp	90	40	1-10/23 Mtrs.	20 Glass	250 Ltrs./Hr.
HE 600	600 x 920 x 870	1 1/4 Hp	150	75	1-12/23 Mtrs.	40 Glass	480 Ltrs./Hr.

* Beer at 25°C input/4°C output in 25°C ambient on peak load.

Confectionery Showcases

The stylish confectionery showcase range from Elanpro comes in multiple shapes and sizes with 3 and 4 layers of display option. Elanpro offers showcases in cold, hot and ambient temperature.



EDC 900 F3 / EDC 1200 F3
EDH 900 F3 / EDH 1200 F3



EDC 900 C2 / EDC 1200 C2
EDH 900 C2 / EDH 1200 C2



EDG 900 C3 / EDG 1200 C3
Grab & Go

Key Features - EDC Series:

- Double tempered with special heated front glass enhances visibility and prevents moisture
- Available in stainless steel & marble finish
- Stainless steel interior
- LED lights on each shelf
- Ventilated refrigeration for uniform cooling
- Danfoss compressor
- Lockable Castors for easy mobility



LSC 408



EHTC & EHTH 160/161
EHTC 100



EDCC 900/1200

Model	Description	Dimension (WxDxH) mm	Temperature Range	No. of Shelves/Pans
LSC 408	4 Side Pastry Showcase	711 x 711 x 1800	2°C ~ 8°C	Base + 4
EDC* 900 C2/F2	Pastry Showcase	900 x 730 x 1200	2°C ~ 10°C	Base + 2
EDC* 1200 C2/F2	Pastry Showcase	1200 x 730 x 1200	2°C ~ 10°C	Base + 2
EDC* 900 C3/F3	Pastry Showcase	900 x 730 x 1300	2°C ~ 10°C	Base + 3
EDC* 1200 C3/F3	Pastry Showcase	1200 x 730 x 1300	2°C ~ 10°C	Base + 3
EDCC 900	Chocolate Showcase	900 x 800 x 1100	2°C ~ 8°C	Base
EDCC 1200	Chocolate Showcase	1200 x 800 x 1100	2°C ~ 8°C	Base
EHTH 160	Countertop Hot Showcase	873 x 570 x 670	30°C ~ 65°C	Base + 2
EHTC 100	Countertop Cold Showcase	700 x 467 x 676	2°C ~ 8°C	Base + 2
EHTC 160/161	Countertop Cold Showcase	873 x 570 x 670	2°C ~ 8°C	Base + 2

Specifications, features and colours are subject to change without any notice, due to continuous product development.
* Hot & ambient model available with same dimension.

30°C ambient temperature / 65% RH

Ice Machines/Flakers

Elanpro offers both under counter Ice machines with built in Storage Bins as well as modular Ice machine with separate Bins. Elanpro ice machines have vertical evaporator and are specially designed for large scale usage such as fast foods, discos, hotels and bars. They are highly relevant for commercial outlets where space is at a premium, they present the best options for bars, coffee shops and restaurants and can also be used for various applications.



EFM 101



Regular Cube
28 x 32 x 22



EIM 101



EIM 41/61 BW*

Key Features:

- Low energy consumption
- Low water consumption per kg of ice produced
- Compatible Ice Storage Bins available separately at an extra cost.
- Air cooled
- Control board with display
- Option of flake & dice shape
- Vertical evaporator
- Stainless steel body
- Adjustable feet
- Pre Filter



EIM 201 / EIM 351 / EIM 501



EIM 1001

Model	EFM 101	EIM 41 BW*	EIM 61 BW*	EIM 101	EIM 201	EIM 351	EIM 501	EIM 1001
Rated Capacity* (Kg/24 hrs)	100	36	55	95	191	318	455	909
Bin Size (Kg)	20	15	18	40	105	125	125	315
Machine Dim. (WxDxH) mm	520 x 550 x 960	500 x 450 x 800	500 x 530 x 850	660 x 685 x 920	560 x 830 x 1718	760 x 830 x 1718	760 x 830 x 1893	1227 x 973 x 2048
Ice Type	Flake	Dice	Dice	Dice	Dice	Dice	Dice	Dice
Cube Size (WxDxH) mm	NA	22 x 22 x 22	28 x 32 x 22	28 x 32 x 22	28 x 28 x 22	28 x 28 x 22	28 x 28 x 22	28 x 28 x 22

* Rated capacity at 10°C Water and 21°C Air. # with online OR bottled water option.

Slush Dispenser



FB X 224

Features

- High density - food grade polycarbonate (PC) bowls
- Liquid crystal display, intelligent temperature control
- Stainless steel evaporator, built-in copper coil, novel appearance, colors are optional
- Super cooling, humanized residual liquid pipe design.
- Applicable to the soda fountain, hotel restaurants, convenience stores, chain restaurant and so on

Model	Capacity (ltrs)	Dimension (WxDxH) mm	Power Watts	Energy Consumption	Weight (kg)
FB XC 112	12	340 x 480 x 820	480	3.3 A	31
FB XC 224	12x2	400 x 480 x 820	900	5.5 A	46
FB XC 336	12x3	600 x 480 x 820	1050	6.0 A	65

Power : 220v/50Hz

Thick Shake Dispenser

A compact counter machine that dispenses cold creams, sherbets and other creamy specialties. Your customer will be captivated by SP, thanks to the perfect consistency of the products it delivers and to its elegant design.



SP 3

Features

- Food-grade polycarbonate (PC) bowls
- Intelligent temperature control
- Stainless evaporator, built-in copper coil
- New appearance, novel and generous
- Super cooling

Model	Capacity (ltrs)	Dimension (WxDxH) mm	Power Watts	Weight (kg)
SP 2	5x2	447 x 438 x 612	500	48
SP 3	5x3	627 x 443 x 612	1000	65

Power : 220v/50Hz

Soft Ice Cream

Elanpro offers two types of soft serve ice cream and frozen yoghurt machine . They come in a range of counter top and floor standing models with dual flavor and twin twist options . Elanpro softy machine offers twin refrigerating chamber to ensure optimum pre cooling and preservation coupled with high capacity freezing cylinder for uninterrupted dispensing.



D 520



D 525

Electrical	D 520	D 525
Voltage	220v/50Hz	220v/50Hz
Rated Input	2300 W	2300 W
Phase	Single	Single
Drive Motor	750 W (1 HP)	750 W (1 HP)
Capacity		
Freezing Cylinder	2 x 1.6 L	2 x 1.75 L
Mix Hopper	2 x 5.5 L	2 x 4.3 L
Production	22 L/Hr	22 L/Hr
Refrigeration		
Refrigerant	R 404 A, 1 HP	R 404 A, 1 HP
Cooling Type	Air-cooled	Air-cooled
Dimensions in mm		
W x D x H	540 x 785 x 800	540 x 720 x 1360
Weight		
Net	115 kg	130 kg

Juice Dispenser



JD LJH 8x2

Features

- Food-grade polycarbonate (PC) bowls
- Intelligent temperature control
- Stainless evaporator, built-in copper coil
- New appearance, novel and generous
- Super cooling

Model	Capacity (ltrs)	Dimension (WxDxH) mm	Power Watts	Energy Consumption	Weight (kg)
JD LP 8x2	8x2	290 x 400 x 680	230	1.6 A	24
JD LJH 16x2	16x2	340 x 485 x 635	260	2.0 A	25

Power : 220v/50Hz

Juice Dispenser



JD LJH 20

Features

- Food-grade polycarbonate (PC) bowl
- Intelligent temperature control
- Stainless evaporator, built-in copper coil
- New appearance, novel and generous
- Super cooling
- Rotating cooling

Model	Capacity (ltrs)	Dimension (WxDxH) mm	Power Watts	Energy Consumption	Weight (kg)
JD LJH 20	20	372 x 412 x 724	180	2.0 A	21

Power : 220v/50Hz

Mini Bar & Mini Fridge

Elanpro Minibars are designed keeping in mind the room aesthetics and noise less cooling performance for your discerning guest.



RB 41 G



RF 61 G



RF 61



RB 41

Key Features - Minibar

- Ammonia refrigerant
- Very low energy consumption
- Silent operation
- Largest range to choose from
 - Sizes : 15 to 60 ltrs
 - Colour : Black, (Brown, & White) (MOQ 200 nos.)
 - Design : Deluxe with solid door & Glass door
 - Designed to perform at 27°C

Key Features - Mini Fridge

- CFC free, R 600a refrigerant
- Low energy consumption and noise
- Available in elegant white colour
- Lock (Optional)
- Designed to perform at 35°C



RF 61



RB 41



RF 60

Model	RB 31	RB 31 G	RB 41	RB 41 G	RF 60/61	RF 61 G
Door Option	Solid	Glass	Solid	Glass	Solid	Glass
Capacity Ltrs.	30	30	40	40	50	50
Input Power (W)	65	65	65	75	80	80
Energy Consumption (Kwh)	0.75	0.75	0.8	0.85	1.05	1.1
Temperature	2°C ~ 10°C					
Dimension (WxDxH) mm	402 x 440 x 500	402 x 428 x 500	402 x 465 x 560	402 x 453 x 560	460 x 480 x 605	460 x 490 x 605
Container (20/40 HC)	240/620	240/620	206/484	206/484	220/575	220/575

Note : Specifications, features and colours are subject to change without any notice, due to continuous product development.

Certifications CE/CB/UL

Retail Solutions - Special Products

Elanpro is pioneer in POS coolers which comprises of counter top coolers & freezers, Can coolers, Check out coolers as well as chocolate coolers. Elanpro coolers are very widely used by top brands like Pepsi, Bisleri, Urja, XXX, Bacardi, Redler, Sting, Nescafe, Baskin Robbins among others.



ECG 85



ECG 60



RF 61 G



ECG 105



ECG 25



SC 60



SD 350/450

For more options and technical details, ask for detailed catalogue.

Product	Counter Top Showcase/Cooler/Freezer/Can Coolers						
Model	ECG 25	ECG 60	ECG 85	ECG 105	SC 60	SD 450	RF 61 G
Dim. (WxDxH) Inch	12 x 14 x 22	17 x 18 x 28	19 x 20 x 32	19 x 21 x 32	18 x 18 x 37	47 x 31 x 48	18 x 19 x 24
Diameter	NA	NA	NA	NA	18	NA	NA
Capacity	25	60	85	105	60	450	50
Temperature range	1°C ~ 8°C				1°C ~ 10°C	-18°C	2°C ~ 10°C
Ambient	35°C	35°C	35°C	35°C	32°C	30°C	35°C
No. of 330ml cans	24	78	105	NA	88	NA	NA
Input Power Watts	80	120	120	120	129	465	80

Electricals : 220V, 50Hz, Single phase specifications, features and colours are subject to change without any notice, due to continuous product development.

Supermarket

Elanpro brings to India most advanced merchandising solution with innovative cooling options applicable for large hyper mart, super marts as well as modern day kirana stores. Leading brands like Big Bazar, Easy day, Nilgiri, More, CCD patronise on Elanpro solution for their display and merchandising application.



ABSS 220 - Multi Deck



EPM 100 / 150 - Multi Deck



Plug-in Multi Deck / Remote Multi Deck
SF 100 / 130 / 200 / 260
RF 188 / 250 / 375



Plug-in Multi Door - Freezer & Chiller
SL2D 131 / SL3D 197 / SL3D 210
SM2D 123 / SM3D 183 / SM4D 245



Remote Multi Door - Freezer & Chiller
RL2D 156 / RL3D 234 / RL4D 312 / RL5D 390
RL2D 123 / RL3D 183 / RL4D 245
RM2D 123 / RM3D 183 / RM4D 245



NSS 1200/1800
Serve Over

Available in a very wide range with various sizes to suit all applications. Our range includes:

1. Multi Door Freezer and Chiller with Plug in and remote unit.
2. Multi deck Chiller with Plug in and remote unit.
3. Serve Over counter
4. Fish display counter

Key Features :

- Low energy consumption
- Designed for Indian condition
- LED Display
- Digital controller with display
- Night curtain in all open units
- High performing refrigeration system
- R404a refrigerant
- Lock in all with door

DESCRIPTION	SF 100	SF 130	SF 200	SF 260	RF 188	RF 250	RF 375	RF 93	RF 125	RF 188	RF 250	SL2D 131	SL3D 197	SL3D 210	SM2D 123	SM3D 183	SM4D 245	RL2D 156	RL3D 234	RL4D 312	RL5D 390	RL2D 123	RL3D 183	RL4D 245	RM2D 123	RM3D 183	RM4D 245	EPM 150	ABSS 220	NSS 1200	NSS 1800
Type	Plug-in Multi Deck				Remote Multi Deck (Slim)			Remote Multi Deck (Regular)				Plug-in Multi Door - Freezer & Chiller						Remote Multi Door - Freezer & Chiller						Multi Deck		Serve Over					
Capacity (Litres)	510	680	1000	1400	1550	2100	3000	520	700	1100	1400	750	1100	1550	750	1100	1550	1400	2100	2800	3500	850	1300	1750	850	1300	1750	1050	NA	NA	NA
Dimension (W) mm	937	1250	1875	2500	1875	2500	3750	937	1250	1875	2500	1310	1970	2100	1230	1835	2450	1560	2340	3120	3900	1230	1835	2450	1230	1835	2450	1560	600	1280	1880
Dimension (DxH) mm	760 x 2000				950 x 2000			760 x 2000				760 x 2000			760 x 2000			950 x 2000			760 x 2000			750 x 1978	500 x 1880	975 x 1285	975 x 1285				
Temperature range - °C					2°C ~ 8°C							≤-18°C			2°C ~ 7°C			≤-18°C			2°C ~ 7°C			2°C ~ 8°C		3°C ~ 7°C					

Electricals : 220V, 50Hz, Single phase specifications, features and colours are subject to change without any notice, due to continuous product development.

Battery Freezer

Elanpro introduces most innovative retail solutions.

Freezer cum Chiller

- Versatile Usage – can be used for Milk and Dairy products in the morning and for Ice Cream/ Frozen food in the afternoon to late night
- Long working hours – power back up of upto 12-14hrs with battery
- Optimum temperature
- Light weight – Helps in larger area coverage
- Round the year utility as can be used for Chilled product even when Ice cream sales reduces
- Low running cost – Less than 5/- per day
- Battery charging time – 5 to 6hrs
- Battery life – 4years



DESCRIPTION	PCF 110	PCF 200	MBF 101	MBF 201
Type	Battery Freezer			
Capacity (Litres)	110	200	110	205
External Dim. (Inch)				
Width	38	41	30	38
Depth	28	25	23	21
Height	28	34	31	32
Baskets / Shelves Qty.	NA	NA	NA	NA
No. of Door	1	2	1	1
Temperature range - °C	-18°C ~ -30°C			
Castors	NA	NA	NA	NA
Lock	NA	NA	NA	NA

Note : Specifications, features and colours are subject to change without any notice, due to continuous product development.

Retail Solutions - Showcase Freezers

Elanpro Flat, Curved Glass Freezers and Island Freezers are known for their performance, aesthetics and low power consumption. All curved glass models are available with LED light or Illuminate Canopy with full basket, while Flat glass come with 70mm insulation, high density basket and are designed to perform at high ambient.

Showcases Freezers - from 55 ltrs. to 650 ltrs.



EKG 155 DC



EKG 55



EKG 315 DL/415 DL

LED Inside



EKG 215 DC



EKG 205A/305A/405A/650
Flat Glass (with optional Canopy)

Scoping Canopy

Key Feature :

- High performing cooling systems
- High insulations
- Low power consumptions
- Heavy duty castors

DESCRIPTION	EKG 155 DC	EKG 215 DC	EKG 315 DL	EKG 415 DL	EKG 625 DL	EKG 55	EKG 205A	EKG 305A	EKG 405A	EKG 650
Type	Curve Glass Top Freezer					Flat Glass Top Freezer				
Capacity (Litres)	155	205	300	400	625	55	205	300	400	650
External Dim. - (Inch)										
Width	23	30	41	48	71	21	37	40	48	71
Depth	27	26	27	27	27	19	23	27	27	27
Height	33	32	36	36	32	18	32	33	33	33
Baskets/Shelves Qty.	2	3	4	5	9	NA	2	2	2	9
No. of Door/Type	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass
Temp. range - °C	-16°C ~ -24°C									
Castors	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes
Canopy (C)/LED (L)	C	C	L	L	L		Optional			

Note : Specifications, features and colours are subject to change without any notice, due to continuous product development.

High Density thickness of 82mm.

Retail Solutions

Presenting Chest Freezers and Chillers with Dual Temperature.

The exciting range of Chest Freezers / Chillers to meet your requirements from 100 ltrs. to 420 ltrs.



EF 106



EF 206 / EF 301



EF 450

Key Feature :

- Low power consumption
- High insulation
- Castors for easy mobility
- Dual temperature - convertible Freezer & Chiller

DESCRIPTION	EF 106	EF 206	EF 301	EF 450
Type	Hard Top Chest Freezer cum Cooler			
Capacity (Litres)	110	227	310	400
External Dim.- (Inch.)				
Width	23	35	44	53
Depth	25	27	25	28
Height	34	35	33	32
Baskets Qty.	1	1	1	2
No. of Door	1	1	1	2
Temperature range - °C	8°C ~ -25°C			
Castors	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes


Note : Specifications, features and colours are subject to change without any notice, due to continuous product development.

Retail Solutions

Elanpro convertible hard top chest freezers conveniently double up as chillers and freezer with the help of a knob and are available in a very pleasing white and grey shades in sizes ranging from 100 to 818 litres to suit every need. You can also choose between single, double and three lid variants.



EF 315 DD



EF 455/EF 475
EF 555/EF 575

Key Feature :

- Low power consumption
- High insulation
- Castors for easy mobility
- Dual temperature - convertible Freezer & Chiller



EF 825



EF 405 (Combi)



DESCRIPTION	EF 135	EF 235	EF 305 D	EF 315 DD	EF 455/475	EF 555/575	EF 825	EF 405 (Combi)
Type	Hard Top Chest Freezer cum Cooler							
Capacity (Litres)	100	220	300	300	410	520	818	175 F + 225 C
External Dim.- (Inches)								
Width	22	32	43	47	52	65	95	55
Depth	23	28	26	24	27	27	29	31
Height	31	33	35	34	35	36	36	39
Baskets Qty.	2	2	2	2	2	2	3	2
No. of Door	1	1	1	2	2	2	3	2
Temperature range - °C	8°C ~ -25°C							
Castors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Note : Specifications, features and colours are subject to change without any notice, due to continuous product development.

Upright Showcase Chiller & Freezer (Frost Free & Static)

Elanpro upright visi coolers & freezers are known for their aesthetics, superior performance and reliability. They come in elegant silver and white finish You can choose from various models starting from 100 to 1500 litre capacities. They come with a Static & Ventilated cooling system with automatic defrost. Elanpro models come with LED lights to enhance the quality of display.



Key Feature :

- LED light
- High performing compressor
- Triple pane heated glass in display freezers
- Castors for easy mobility
- Lock

DESCRIPTION	EFS 245	EFS 340	EFSV 340	EFGV 205	EFGV 400	EFGV 450	EFGV 1000	EFGV 1500	ECSV 370	ECG 105	ECG 205	ECG 305	ECG 405	ECG 630 DD	ECG 1100 A	ECG 1500
Type	Upright Freezer#								Upright Chiller							
Capacity (Litres)	245	340	340	200	400	450	950	1500	370	100	200	300	400	630	1100	1500
External Dim. (Inch)																
Width	22	24	24	18	26	27	54	81	23	19	20	22	26	40	47	81
Depth	24	25	25	24	26	28	28	28	25	21	23	24	26	24	28	28
Height	57	73	73	71	83	78	78	78	73	32	54	66	76	80	80	78
Shelves Qty	5	7	7	10	4	4	8	12	5	2	3	4	4	8	8	12
No. of Door	1	1	1	1	1	1	2	3	1	1	1	1	1	2	2	3
Temperature °C	-16°C ~ -24°C			-16°C ~ -24°C			-18°C ~ -22°C			1°C ~ 10°C						
Castors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	NA	Yes	Yes	Yes	Yes	Yes	Yes
Lock	No	No	No	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Electricals : 220V, 50Hz, Single phase specifications, features and colours are subject to change without any notice, due to continuous product development.

* At 32°C ambient