

REFRIGERATION SOLUTIONS TO HELP YOUR BUSINESS DO BETTER.





BLUE STAR REACH-IN CHILLERS & FREEZERS.

EASY STORAGE MEETS ACCURATE TEMPERATURE CONTROL.



Features



Tropicalised for high ambient temperatures



Food grade stainless steel unit



Uniform cooling by



forced air circulation



Adjustable tray slides



Rounded corners

Eco-friendly

refrigerant

Odourless operation

due to continuous

Self-closing doors

air circulation



Auto defrost



LED Light



for visibility



Removable gasket for easy cleaning



surface. These units can also be offered with the option of SS shelves.

Technical Specification

Reach-in Freezers						
Description	RF2D700GP	RF4D1450GP	RF2D700GC	RF4D1450GC	RF2D550N*	RF4D1100N*
Capacity (Ltrs)	650	1350	650	1350	600	1200
Temperature Range	-20° to -7°C	-20º to -7ºC	-20º to -7ºC	-20º to -7ºC	–18º to –10ºC	-18º to -10ºC
No. of Doors	2	4	2	4	2	4
Type of Doors (Int/Ext)	SS-304/201	SS-304/201	SS-201/201	SS-201/201	SS201/SS201	SS201/SS201
Shelves Qty	3	6	3	6	3	6
Light	Yes	Yes	Yes	Yes	No	No
Refrigerant Gas (Type/Charge)	R290/115g	R290/120g x 2	R290/115g	R290/120g X 2	R290/110g	R290/150g
Voltage & Frequency (V–Hz)	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220/240V-50Hz	220/240V-50Hz
Power (Watts)	522	950	522	950	400	608
Current (Amps)	2.6	4.9	2.6	4.9	4.2	8.9
Defrost	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Temperature Display LED	Yes	Yes	Yes	Yes	Yes	Yes
External Dimension (W x D X H) mm	700 x 880 x 2043	1400 x 880 x 2043	700 x 880 x 2043	1400 x 880 x 2043	700 x 765 x 1997	1200 x 760 x 1997
Net Weight (kg)	119	200	119	200	85	90
Gross Weight (kg)	129	214	129	214	120	130

Reach-in Chillers						
Description	RC2D700GP	RC4D1450GP	RC2D700GC	RC4D1450C	RC2D550N*	RC4D1100N*
Capacity (Ltrs)	650	1350	650	1350	600	1200
Temperature Range	0º to +12ºC	0º to +12ºC	0º to +12ºC	0º to +12ºC	0º to +10ºC	0º to +10ºC
No. of Doors	2	4	2	4	2	4
Type of Doors (Int/Ext)	SS-304/201	SS-304/201	SS-201/201	SS-201/201	SS201/SS201	SS201/SS201
Shelves Qty	3	6	3	6	3	6
Light	Yes	Yes	Yes	Yes	No	No
Refrigerant Gas (Type/Charge)	R290/90g	R290/120g	R290/90g	R290/120g	R290/100g	R290/150g
Voltage & Frequency (V–Hz)	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220/240V-50Hz	220/240V-50Hz
Power (Watts)	250	600	250	600	300	490
Current (Amps)	1.3	3.3	1.3	3.3	3.2	5.5
Defrost	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Temperature Display LED	Yes	Yes	Yes	Yes	Yes	Yes
External Dimension (W x D X H) mm	700 x 880 x 2043	1400 x 880 x 2043	700 x 880 x 2043	1400 x 880 x 2043	700 x 765 x 1997	1200 x 760 x 1997
Net Weight (kg)	112	190	112	190	85	90
Gross Weight (kg)	122	204	122	204	120	130

^{*}Non GN compatible

BLUE STAR UNDER COUNTER CHILLERS & FREEZERS.

HIGH PERFORMANCE COMES WITH A HEAVY-DUTY BUILD.



Features



Tropicalised for high ambient temperatures



Uniform cooling by forced air circulation



Digital temperature indicator



Auto defrost



Eco-friendly refrigerant



Self-closing



doors



Adjustable



tray slides



Adjustable feet



Food grade stainless steel



Odourless operation due to continuous air circulation



Removable gasket for easy cleaning



Door options: stainless steel / glass

Technical Specification

Undercounter Chillers						
Description	UC2100GP	UC3100GP	UC2100GC	UC3100GC		
Capacity (Ltrs)	260	400	260	400		
Temperature Range	0º to +12ºC	0º to +12ºC	0º to +12ºC	0º to +12ºC		
No. of Doors	2	3	2	3		
Cabinet and Doors (Int/Ext)	SS-304/201	SS-304/201	SS-201/201	SS-201/201		
Shelves Qty	2	3	2	3		
Gn Pan	GN2/1	GN2/1	GN2/1	GN2/1		
Refrigerant Gas (Type/Charge)	R290/50g	R290/50g	R290/50g	R290/50g		
Voltage supply & Frequency (V–Hz)	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz		
Max Input Power	255W	255W	255W	255W		
Current Amps	1.3	3.3	1.3	3.3		
Defrost	Automatic	Automatic	Automatic	Automatic		
Thermostat	Digital	Digital	Digital	Digital		
External Dimension (W x D X H) mm	1365 x 700 x 850	1805 x 700 x 850	1365 x 700 x 850	1805 x 700 x 850		
Net Weight (kg)	96	116	96	116		
Gross Weight (kg)	115	142	115	142		

Undercounter Freezers						
Description	UF2100GP	UF3100GP	UF2100GC	UF3100GC		
Capacity (Ltrs)	260	400	260	400		
Temperature Range	−20° to −7°C	−20° to −7°C	−20° to −7°C	−20° to −7°C		
No. of Doors	2	3	2	3		
Cabinet and Doors (Int/Ext)	SS-304/201	SS-304/201	SS-201/201	SS-201/201		
Shelves Qty	2	3	2	3		
Gn Pan	GN2/1	GN2/1	GN2/1	GN2/1		
Refrigerant Gas (Type/Charge)	R290/140g	R290/140g	R290/140g	R290/140g		
Voltage supply & Frequency (V–Hz)	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz		
Max Input Power	510W	510W	510W	510W		
Current Amps	2.5A	2.5A	2.5A	2.5A		
Defrost	Automatic	Automatic	Automatic	Automatic		
Thermostat	Digital	Digital	Digital	Digital		
External Dimension (W x D X H) mm	1365 x 700 x 850	1805 x 700 x 850	1365 x 700 x 850	1805 x 700 x 850		
Net Weight (kg)	106	126	106	126		
Gross Weight (kg)	125	152	125	152		

BLUE STAR SALADETTES AND SANDWICH STATIONS.

EXCEPTIONAL EFFICIENCY AND ROBUST CONSTRUCTION.



Features



Easy serviceability



Curved edge for easy cleaning



High efficiency and functionality



Automatic defrost



Green refrigerant



Adjustable feet



Self-closing doors



Removable gasket





45mm thick insulation



Digital temperature control

Saladettes and Sandwich Stations					
Description	SC2100GA	SC3100GA			
Capacity (Ltrs)	260	400			
No. of Doors (Nos.)	2	3			
Type of Doors (Int/Ext)	SS-201/201	SS-201/201			
Temperature Range OC	2º to +8ºC	2º to +8ºC			
Shelves Qty (Nos.)	2	3			
Gn Pan	GN2/1	GN2/1			
Toppings Pan Slot	YES	YES			
Refrigerant Gas (Type/Charge)	R290/55g	R290/60g			
Voltage supply & Frequency (V–Hz)	220-240V/50Hz	220-240V/50Hz			
Max Input Power	143W	152W			
Current Amps	1.1A	1.5A			
Defrost	Automatic	Automatic			
Thermostat	Digital	Digital			
External Dimension (W x D X H) mm	900 x 700 x 990	1365 x 700 x 990			
Net Weight (kg)	72	110			
Gross Weight (kg)	83	130			

BLUE STAR BLAST FREEZERS.

RAPID COOLING SOLUTIONS FOR PRESERVING FOOD QUALITY.

Blue Star offers a new range of Blast Freezers ideal for extremely fast chilling needs. These freezers help eliminate contamination from bacteria and maintain the quality of food products. A must-have product for any kitchen, they also prevent any weight loss of food products.

Features





Electronic temperature display



-ot-Tropicalised for Indian conditions



High performance





Time and probe based chiller and freezer temperature setting

Blast Chillers & Freezers						
Description	BF05G	BF10G	BF15G			
Cooling Type	Chiller & Freezer	Chiller & Freezer	Chiller & Freezer			
Chilling Volume (Kg)	18	34	50			
Freezing Volume (Kg)	11	22	38			
Phase	Single	Single	Three			
Chilling Temp °C	+90°C \ +3°C	+90°C / +3°C	+90°C / +3°C			
Freezing Temp °C	+90°C / -33°C	+90°C / -33°C	+90°C / -33°C			
Prop	1 Nos.	1 Nos.	1 Nos.			
Defrost	Automatic	Automatic	Automatic			
Temperature Display	Digital	Digital	Digital			
Door	Solid Door	Solid Door	Solid Door			
Voltage Supply & Frequency (V – Hz)	230V/50Hz	230V/50Hz	400V/50Hz			
Max Input Power	1185W	2010W	3820W			
Refrigerant Gas (Type/Charge)	R404a/850G	R404a/1600G	R404a/2400G			
Shelf	5 Gn1/1	10 Gn1/1	15 Gn1/1			
External Dimension (W x D x H) mm	800 x 700 x 900	800 x 780 x 1700	800 x 780 x 2000			
Net Weight (Kg)	92	145	175			
Gross Weight (Kg)	112	168	185			



BLUE STAR BACK BAR CHILLER.

OUTSTANDING VISIBILITY WITH SPACE-SAVING DESIGN.

lue Star offers Back Bar Chiller options that can be used at any bar, club and/or restaurant. With glass oors, they provide excellent visibility and are designed to save space. Storage in these chillers ensures reat preservation and convenient, ready—to—serve drinks.

Features



Self-closing doors



Digital temperature control



Internal LED light for better visibility



Replaceable gasket



Lock fitted as standard



Adjustable shelves and feet



Safety tempered glass and double glazed doors

Back Bar Chiller					
Description	BC250A	BC350A			
Capacity (Ltrs)	190	320			
Cooling Type	Ventilated	Ventilated			
No. of Doors (Nos.)	2	3			
Type of Doors	Glass Door	Glass Door			
Temperature Range °C	1 to +10°C	1 to +10°C			
Shelves Qty/Colour/Adjustable	4 / White	6 / White			
Refrigerant Gas (Type/Charge)	R600a/70g	R600a/90g			
Voltage Supply & Frequency (V – Hz)	220-240V/50Hz	220-240V/50Hz			
Max Input Power	210W	345W			
Defrost	Automatic	Automatic			
External Dimension (W x D x H) mm	900 x 520 x 900	1350 x 520 x 900			
Net Weight (Kg)	62	80			
Gross Weight (Kg)	65	87.5			



BLUE STAR ICE MACHINES.

ICE OF ANY SHAPE. FOR ANY OCCASION.

10 (1.11) DAME STAR Blue Star, India's leading air conditioning and retrigeration company, extends its category to bring you sophisticated ice—making machines that freeze water and make ice effectively. These machines are hygienic, energy efficient, durable and easy to maintain. Blue Star uses its expertise and domain knowledge to give you the products as per your needs and requirements. And with its widespread service network you can be sure of long life and optimum performance from your machine.



Features



Power saving design



Auto stop and start



Perfectly shaped ice



Equipped with sprayers for easy cleaning



Water content control



Compact design saves space



Stainless steel body for longer life



Designed for noiseless operation

Ice Machines					
MODEL NAME	ICM-15	ICM-20	ICM-26	ICM-50	ICM-90
Production in 24hrs	15kg	20kg	26kg	50kg	80kg
Storage capacity	1.4kg	3.5kg	6kg	10kg	42kg
Cooling System	Air Cooled				
Type of Ice	Bullet ice	Bullet ice	Bullet ice	Bullet ice	Gourmet
Mass of Ice	10g	15g	15g	15g	25g
Refrigerant	R600a	R600a	R600a	R290	R290
Voltage / Frequency / Phase	220-240V-50Hz/1Ph	220-240V-50Hz/1Ph	220-240V-50H2/1Ph	220-240V-50Hz/1Ph	220-240V-50Hz/1Ph
Rated Power	126W	178W	250W	295W	670W
Product Dimension (WxDxH)	420x465x470 mm	440x530x647 mm	470x585x710 mm	570x665x896 mm	780x650x1045 mm
Net weight	17kg	27kg	33kg	45.5kg	63.5kg

BLUE STAR PASTRY SHOWCASE.

SO STYLISH IT MAKES THE GOOD EVEN BETTER.

Blue Star's Pastry Showcase suits any environment without compromising on style and display area. Its unique design enhances the appearance of cookies, cakes, brownies, and more items and attracts the eyes of everyone who passes by. The showcase features advanced technology with low emissivity tempered glass for clear product visibility, preventing frost formation.



Features



Tempered and low emissivity glass for unlimited visibility



4 Castor wheels, 2 with brakes



3 Nos. glass shelves



Brilliant LED lighting



Ventilated refrigeration for uniform cooling



Available in different sizes (in feet): 3,4,5,6



Consumes less energy



Elegant finish

Description	KORAL 09CSQP	KORAL 12CSQP	KORAL16CSQP	KORAL 18CSQP
Function	Chiller	Chiller	Chiller	Chiller
Structure	Square	Square	Square	Square
Size In Ft	3	4	5	6
Temp Range OC	2ºC to +8ºC	2ºC to +8ºC	2ºC to +8ºC	2ºC to +8ºC
Voltage/frequency	220V~240V~50Hz	220V~240V~50Hz	220V~240V~50Hz	220V~240V~50Hz
Refrigerant	R290	R290	R290	R290
Castor Wheels	Yes	Yes	Yes	Yes
Inner Material	SS201 – Food Safe			
Shelf Nos.	3	3	3	3
Side Panel	Tempered Glass	Tempered Glass	Tempered Glass	Tempered Glass
Marble Base	Optional	Optional	Optional	Optional
Light	Yes	Yes	Yes	Yes
Dimension (WxDxH) In mm	900x750x1200	1200×750×1200	1500×750×1200	1800×750×1200
Weight In Kg	130	167	204	240