



WDE-100

Commercial Dehumidifier

Technical Specification: -

- Model No.: - WDE-100
- Moisture removal 30°C, 80%R.H.: - 100 L/Day
- Power supply V/Hz: - 220~240V/50Hz
- Rated Power consumption 30°C, 80%R.H.: - 1400W
- Control Type;- Electric
- Maintain level: - 30% R.H.- 80% R.H.
- Current 30°C, 80%R.H.: - 5 A
- Air flow/Air Circulation: -700m³/hr
- Ambient Temperature for operation: -
- Approx. Cover Area*: -
- Noise level: -
- Refrigerant: -
- Net Weight: -
- Body dimensions (H x W x D): -

5-32°C
 45~230m²(height=2.6m)
 54 dB(A)
 R290
 41 kgs
 872 x 540x 388 mm / 34.22 x 21.25 x 15.27 inch

Features:

- Rotary compressor
- Standard colour sheet metal casing,
- Automatic defrost
- Humidity setting
- Sensor fault indicator function
- Washable filter
- Continuous drainage with external hose.
- Automatic humidistat Control.
- Portable easy to carry handle
- Easily move on wheels.

Perfect Airconditioning Trading Company

A-269 Okhla Industrial Area-I ,New Delhi-110020, India Tel:011-26817098,26817099,26811831,26811832,41811832

Email: ac@tripti.in Website: www.tripti.in