



## WDE-110S

### Commercial Dehumidifier

#### Features:

- Rotary compressor
- Stainless steel Shell
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- With Water Tank & Drain Pump.
- Option for Continuous drainage with external hose.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

#### Technical Specification: -

• Model No.:	-	WDE-110S
• Moisture removal 30°C, 80%R.H.:	-	110L/Day
• Power supply V/Hz:	-	220~240V/50Hz
• Rated Power consumption 30°C, 80%R.H.:	-	1450W
• Control Type;	-	Electric
• Maintain level:	-	30% R.H.- 80% R.H.
• Current 30°C, 80%R.H.:	-	6.6A
• Air flow/Air Circulation:	-	950m <sup>3</sup> /hr
• Ambient Temperature for operation:	-	5-38°C
• Approx. Cover Area*:	-	100~130m <sup>2</sup> (height=2.6m)
• Noise level:	-	60 dB(A)
• Refrigerant:	-	R410
• Net Weight:	-	50 kgs
• Body dimensions (H x W x D):	-	1010 x 480 x 410 mm / 39.76 x 18.90 x 16.14 inch

Perfect Airconditioning Trading Company

A-269 Okhla Industrial Area-I ,New Delhi-110020, India Tel:011-26817098,26817099,26811831,26811832,41811832

Email: ac@tripti.in Website: www.tripti.in