



WDE-150S Commercial Dehumidifier

Features:

- Rotary compressor
- Stainless Steel Shell
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- With Water Tank & Drain Pump
- Option for Continuous drainage with external hose.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

Technical Specification: -

- | | | |
|--|---|--|
| • Model No.: | - | WDE-150S |
| • Moisture removal 30°C, 80%R.H.: | - | 150L/Day |
| • Power supply V/Hz: | - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: | - | 1.7kW |
| • Control Type; | - | Electric |
| • Maintain level: | - | 30% R.H.- 80% R.H. |
| • Current 30°C, 80%R.H.: | - | 8.1A |
| • Ambient Temperature for operation: | - | 5-38°C |
| • Refrigerant: | - | R410 |
| • Net Weight(Approx.): | - | 54 kgs |
| • Body dimensions (H x W x D): | - | 1010 x 480 x 410 mm / 39.76 x 18.90 x 16.14 inch |

Perfect Airconditioning Trading Company
A-269 Okhla Industrial Area-I ,New Delhi-110020, India Tel:011-26817098,26817099,26811831,26811832,41811832
Email: ac@tripti.in Website: www.tripti.in