



WDE-603T

Commercial Dehumidifier

Features:

- Rotary compressor
- Standard colour sheet metal casing,
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- With 7 ltrs. Tank.
- Continuous drainage option available.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

Technical Specification: -

- | | | |
|--|---|---|
| • Model No.: | - | WDE-603T |
| • Moisture removal 30°C, 80%R.H.: | - | 60L/Day |
| • Power supply V/Hz: | - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: | - | 820W |
| • Control Type; | - | Electric |
| • Maintain level: | - | 30% R.H.- 80% R.H. |
| • Current 30°C, 80%R.H.: | - | 3.5A |
| • Air flow/Air Circulation: | - | 550m ³ /hr |
| • Ambient Temperature for operation: | - | 5-38°C |
| • Water tank capacity: | - | 7 Litres |
| • Approx. Cover Area*: | - | 50~120m ² (height=2.6m) |
| • Noise level: | - | 60 dB(A) |
| • Refrigerant: | - | R410 |
| • Net Weight: | - | 35 kgs |
| • Body dimensions (H x W x D): | - | 680 x 372 x 394 mm / 26.77 x 14.65 x 15.51 inch |